

CBS-XR6550D Dual-source Dual-view X-ray Security Inspection Machine

The CBS-XR6550D dual-source dual-view security inspection machine uses two independent detection systems to simultaneously capture image data from horizontal and vertical directions. The images are displayed through a dual-screen control console, effectively reducing missed detections and false alarms. The product is widely used in courts, procuratorates, subway stations, and inspection checkpoints.



Key Features

Modular Design

The internal circuitry adopts a modular design with optimized layout, effectively improving anti-interference capability, ensuring stable operation, and facilitating maintenance.

Digital Technology

The hardware system adopts an advanced ASIC-based fully digital design combined with in-depth data acquisition technology. Compared with conventional analog acquisition systems, it offers higher integration, stronger anti-interference capability, and clearer imaging performance.

Intelligent Functions

The system integrates multiple intelligent functions, including RTOS-based real-time image processing, TIP (Threat Image Projection) for threat simulation, auxiliary alarm for suspicious items, remote control and management, as well as fast image storage and backup.

Professional Focus, Targeted Concentration, Quality Priority, Constant Innovation

High ambition,sight further Zhonghaoyue Technology (Shenzhen) Co., Ltd.

Automated Operation

The system features automated functions including one-touch power on and off, infrared energy-saving sensing, emergency alarm alerts, as well as automatic fault self-diagnosis, ensuring efficient and reliable operation.

Professional Design

The system is designed with a user-friendly interface, efficient and practical image processing functions, and a customized dedicated security inspection keyboard, providing a professional and convenient user experience.

Basic Specifications

Chamber Dimensions:	655 × 505 mm (W × H)	Conveyor belt speed:	0.25m/s
Conveyor belt load capacity:	250kg (uniform load)	Steel penetration:	≥38 mm (Horizontal/Vertical)
Wire resolution:	> 38 AWG(Horizontal/Vertical)	Spatial resolution:	1.0 mm (Horizontal/Vertical)

X-ray Source

Control Interface:	Analog Interface	Tube Voltage:	140 ~ 160 kV (adjustable)
Tube Current:	0.6 ~1.2 mA (adjustable)	Cooling Method:	Sealed oil cooling with industrial forced air cooling
Duty Cycle:	100%, no warm-up required	Protection Functions:	Overvoltage, overcurrent and overtemperature protection

Radiation Safety Indicators

Leakage dose rate:	< 0.5 μGy/h (at a distance of 5 cm from the casing)	Single dose:	< 1.0 μGy
Safety:	Safe for photographic film, chips and electronic devices		
Radiation Shielding:	The entrance and exit of the passage are shielded with a double-layer, eco-friendly lead curtain (0.5 mm Pb), while the main body is shielded with 2–6 mm lead plates, ensuring that external radiation from the equipment complies with national safety standards		

Installation Data

Noise Level:	< 55 dB(A)	Weight:	900 kg (including wooden crate)
Power Consumption:	0.8 kW (MAX)	Power supply:	AC 220 V ±10%, 60 Hz ±5 Hz
Passage Height:	680mm	Dimensions:	2400 mm (L) × 1320 mm (W) × 1400 mm (H)
Crate Dimensions:	2510 mm (L) × 1380mm (W) × 1560 mm (H)		

Control Console

Type:	Dual-screen control console	Weight:	150 kg (including wooden crate)
Dimensions:	1200 mm (L) × 750 mm (W) × 1260 mm (H)		
Crate Dimensions:	1270 mm (L) × 830 mm (W) × 1400 mm (H)		
Optional Modules 1、Multi-angle monitoring system 2、Remote operation management system 3、Dedicated security inspection keyboard 4、Energy-saving sensor 5、Adjustable-speed conveyor belt 6、Extended entry/exit item collection table 7、Face recognition			